

R and PL Series Warranty Policy

Champion warrants each new compressor pump in these series manufactured by Champion, mounted on a factory assembled unit, to be free from defects in material and workmanship under normal use and service for a period of sixty (60) months from date of installation or sixty-six (66) months from date of shipment by Champion or Champion distributor, whichever may occur first. Applies to the compressor pump only, excluding head valves. Valves, controls and accessories are warranted for the first year only. Compressor pumps purchased separately would carry a one year warranty. The five year extended warranty will be prorated over the 5 years as follows:

First Year	100% Allowance, Parts and Labor
Second Year	90% Allowance, Parts and Labor
Third Year	80% Allowance, Parts and Labor
Fourth Year	70% Allowance, Parts and Labor
Fifth Year	60% Allowance, Parts and Labor

Applies to Champion logo, tank or base mounted complete compressors only.

Express Limited Warranty

Champion warrants each new air compressor unit manufactured by Champion to be free from defects in material and workmanship under normal use and service for a period of twelve (12) months from date of installation or eighteen (18) months from date of shipment by Champion or Champion distributor, whichever may occur first.

Champion makes no warranty in respect to components and accessories furnished to Champion by third parties, such as electric motors, gasoline engines and controls, which are warranted only to the extent of the original manufacturer's warranty to Champion. To have warranty consideration, electric motors must be equipped with thermal overload protection.

The extended five year warranty will apply to ASME air receivers provided they are installed on rubber vibro isolator pads or approved equivalent.

When a compressor pump, or component is changed or replaced during the warranty period, the new/replaced item is warranted for only the remainder of the original warranty period.

Repair, replacement or refund in the manner and within the time frame provided shall constitute Champions sole liability and the Purchasers exclusive remedy resulting from any nonconformity or defect. Champion shall not in any event be liable for any damages, whether based on contract , warranty, negligence, strict liability or otherwise, including without limitation any consequential, incidental or special damages arising with respect to the equipment or its failure to operate, even if Champion has been advised of the possibility thereof.

Champion makes no other warranty or representation of any kind, except that of title, and all other warranties, express or implied, including warranties or merchantability and fitness for a particular purpose, are hereby expressly disclaimed. No salesman or other representative of Champion has authority to make any warranties.

Owner's Responsibilities

SAFETY:

The Operation/Maintenance Manual accompanying this piece of equipment contains important safety information and must be made available to those operating this equipment. Operator must also read, understand & retain the information given in the various safety labels affixed to the unit.

INSTALLATION:

Compressor must be located in a clean, well-ventilated, dry room to insure an adequate supply of fresh, clean, cool and dry air.

Compressor flywheel should have a minimum clearance of 12" from any obstruction to insure proper cooling of unit.

Lagging compressor to the floor is required. It is essential to shim the legs to avoid undue stress on the tank welds. Lag bolts should be "snug", but not tight. For 5 year tank warranty to apply, it is required that the tank be mounted on vibro isolator pads placed under the tank feet.

Necessary electrical wiring and connections should be made by a qualified electrician and must be installed in accordance with all national and local electrical codes. Pressure relief valves and pressure switches must not be tampered with have their settings changed under any conditions.

MAINTENANCE:

Refer to owner's manual for safety rules and detailed maintenance instructions and service schedule.

- Keep oil level at the full mark.
- Change oil as required.
- Drain moisture from tank daily.
- Keep complete unit clean.
- Keep intake filters and valves clean. Inspect valves every 90 days.
- Pull ring on all pressure relief valves every 3 months to assure proper operation.
- Keep belts adjusted properly.
- Keep nuts, bolts, capscrews and all fittings tight.

Failure of owner to comply with safety rules, installation and maintenance procedures outlined above, and in the Operation/Maintenance Manual, will void warranty.

FREIGHT DAMAGE:

Freight damages do not constitute warranty or service adjustment. Champion's terms are FOB point of shipment/factory, and Champion's responsibility ceases upon delivery of material to carrier and obtaining receipt for same. It is the responsibility of the receiving customer to file damage, shortage or concealed damage claim with the delivering carrier on receipt of material.